

WHAT IS CLAIMED IS:

1. An optical film comprising diffraction grating cells arranged in a matrix, each cell comprising blazed type or binary type curved gratings.

5 2. The optical film according to claim 1, wherein said gratings contain different profiles.

3. The optical film according to claim 1, wherein said gratings contain the same profile and arranged in parallel with each other.

10 4. The optical film according to one of claims 1 to 3, wherein said gratings include at least two grating pitches.

15 5. The optical film according to one of claims 1 to 3, wherein an angle of a slope of the gratings is uniform.

6. The optical film according to one of claims 1 to 3, wherein a surface of said diffraction grating cells is provided with a reflection layer.

20 7. The optical film according to one of claims 1 to 3, wherein the grating has a gentle slope and a steep slope in a cross section and a surface of the gentle slope is provided with a reflection layer.

25 8. The optical film according to one of claims 1 to 3, wherein fine rectangular or elliptic projections or recesses are formed on a surface of said diffraction grating cells with a short axis thereof agreeing with a direction of juxtaposition of said gratings.

9. A display device comprising:

a liquid crystal display layer which forms an image to be displayed; and

5 a light reflecting optical film which is arranged on a rear surface of the liquid crystal display layer and comprises diffraction grating cells arranged in a matrix, each cell comprising blazed type or binary type curved gratings.

10 10. The display device according to claim 9, wherein said gratings contain different profiles.

11. The display device according to claim 9, wherein said gratings contain the same profile and arranged in parallel with each other.

15 12. The display device according to one of claims 9 to 11, wherein said gratings include at least two grating pitches.

13. The display device according to one of claims 9 to 11, wherein an angle of a slope of the gratings is uniform.

20 14. The display device according to one of claims 9 to 11, wherein a surface of said diffraction grating cells is provided with a reflection layer.

25 15. The display device according to one of claims 9 to 11, wherein the grating has a gentle slope and a steep slope in a cross section and a surface of the gentle slope is provided with a reflection layer.

16. The display device according to one of

claims 9 to 11, wherein fine rectangular or elliptic projections or recesses are formed on a surface of said diffraction grating cells with a short axis thereof agreeing with a direction of juxtaposition of said gratings.

17. The display device according to one of claims 9 to 11, wherein

said liquid crystal display layer comprises pixels arranged in a matrix; and

said diffraction grating cells and said pixels show a one-to-one correspondence.

18. The display device according to one of claims 9 to 11, wherein

said liquid crystal display layer comprises pixels arranged in a matrix; and

a pitch of arrangement of said diffraction grating cells is integer times of a pitch of arrangement of said pixels or vice versa.

19. The display device according to one of claims 9 to 11, wherein the grating has a gentle slope and a steep slope in a cross section and the gentle slope is directed to above a display screen of said display device.

20. A display device comprising:

a liquid crystal display layer which forms an image to be displayed; and

a light transmission optical film which is

arranged on a front surface of the liquid crystal display layer and comprises diffraction grating cells arranged in a matrix, each cell comprising blazed type or binary type curved gratings.

5 21. The display device according to claim 20, wherein said gratings contain different profiles.

 22. The display device according to claim 20, wherein said gratings contain the same profile and arranged in parallel with each other.

10 23. The display device according to one of claims 20 to 22, wherein said gratings include at least two grating pitches.

 24. The display device according to one of claims 20 to 22, wherein an angle of a slope of the gratings is uniform.

15 25. The display device according to one of claims 20 to 22, wherein fine rectangular or elliptic projections or recesses are formed on a surface of said diffraction grating cells with a short axis thereof agreeing with a direction of juxtaposition of said gratings.

20 26. The display device according to one of claims 20 to 22, wherein

 said liquid crystal display layer comprises pixels arranged in a matrix; and

25 said diffraction grating cells and said pixels show a one-to-one correspondence.

27. The display device according to one of claims 20 to 22, wherein

said liquid crystal display layer comprises pixels arranged in a matrix; and

5 a pitch of arrangement of said diffraction grating cells is integer times of a pitch of arrangement of said pixels or vice versa.

10 28. The display device according to one of claims 20 to 22, wherein the grating has a gentle slope and a steep slope in a cross section and the gentle slope is directed to above a display screen of said display device.

15 29. The display device according to one of claims 20 to 22, wherein fine rectangular or elliptic projections or recesses are formed on a surface of said diffraction grating cells with a short axis thereof agreeing with a direction of juxtaposition of said gratings.

20 30. An optical film comprising:
diffraction grating cells arranged in a matrix,
each cell comprising curved gratings, wherein said gratings include at least two grating pitches.

25 31. The optical film according to claim 30, wherein said diffraction grating cells are blazed type diffraction grating cells.

32. The optical film according to claim 30, wherein said diffraction grating cells are binary type

diffraction grating cells.

33. The optical film according to one of claims 30 to 32, wherein, a pitch d_y of arrangement of the gratings is changed in a cell so as to change either
5 α_y or the tangent of α_y stepwise by a constant value, wherein θ is an angle in the vertical direction at which incident light enters the diffraction grating cells, α_y is an angle in the vertical direction at which diffracted light emits from the diffraction
10 grating cells, and $\lambda (= d_y \times (\sin \theta + \sin \alpha_y))$ is a wavelength of diffracted light.

34. The optical film according to one of claims 30 to 32, wherein a pitch of arrangement of the gratings in a diffraction grating cell is constant and a pitch
15 d_y of arrangement of the gratings is changed from cell to cell so as to change either α_y or the tangent of α_y stepwise by a constant value, wherein θ is an angle in the vertical direction at which incident light enters the diffraction grating cells, α_y is an angle in the
20 vertical direction at which diffracted light emits from the diffraction grating cells, and $\lambda (= d_y \times (\sin \theta + \sin \alpha_y))$ is a wavelength of diffracted light.

35. The optical film according to one of claims 30 to 32, wherein a pitch of arrangement of the gratings
25 in a diffraction grating cell is constant and there are at least two grating pitches of arrangement of the gratings among the diffraction grating cells, a

and comprises diffraction grating cells arranged in a matrix, each cell comprising curved gratings, wherein said gratings include at least two grating pitches.

42. The display device according to claim 41,
5 wherein said gratings contain different profiles.

43. The display device according to claim 41,
wherein said gratings contain the same profile and arranged in parallel with each other.

44. The display ~~device~~ according to one of
10 claims 41 to 43, wherein said gratings include at least two grating pitches.

45. The display device according to one of
claims 41 to 43, wherein an angle of a slope of the gratings is uniform.

46. The display device according to one of
15 claims 41 to 43, wherein a surface of said diffraction grating cells is provided with a reflection layer.

47. The display device according to one of
claims 41 to 43, wherein the grating has a gentle slope
20 and a steep slope in a cross section and a surface of the gentle slope is provided with a reflection layer.

48. The display device according to one of
claims 41 to 43, wherein fine rectangular or elliptic
projections or recesses are formed on a surface of said
25 diffraction grating cells with a short axis thereof agreeing with a direction of juxtaposition of said gratings.

49. The display device according to one of claims 41 to 43, wherein

said liquid crystal display layer comprises pixels arranged in a matrix; and

5 said diffraction grating cells and said pixels show a one-to-one correspondence.

50. The display device according to one of claims 41 to 43, wherein

10 said liquid crystal display layer comprises pixels arranged in a matrix; and

a pitch of arrangement of said diffraction grating cells is integer times of a pitch of arrangement of said pixels or vice versa.

15 51. The display device according to one of claims 41 to 43, wherein the grating has a gentle slope and a steep slope in a cross section and the gentle slope is directed to above a display screen of said display device.

52. A display device comprising:

20 a liquid crystal display layer which forms an image to be displayed; and

a light transmission optical film which is arranged on a front surface of the liquid crystal display layer and comprises diffraction grating cells
25 arranged in a matrix, each cell comprising blazed type or binary type curved gratings.

53. The display device according to claim 52,

11/22/2009

OK
A2

wherein said gratings contain different profiles.

54. The display device according to claim 52, wherein said gratings contain the same profile and arranged in parallel with each other.

5 55. The display device according to one of claims 52 to 54, wherein said gratings include at least two grating pitches.

10 56. The display device according to one of claims 52 to 54, wherein an angle of a slope of the gratings is uniform.

15 57. The display device according to one of claims 52 to 54, wherein fine rectangular or elliptic projections or recesses are formed on a surface of said diffraction grating cells with a short axis thereof agreeing with a direction of juxtaposition of said gratings.

58. The display device according to one of claims 52 to 54, wherein

20 said liquid crystal display layer comprises pixels arranged in a matrix; and

said diffraction grating cells and said pixels show a one-to-one correspondence.

59. The display device according to one of claims 52 to 54, wherein

25 said liquid crystal display layer comprises pixels arranged in a matrix; and

a pitch of arrangement of said diffraction grating

cells is integer times of a pitch of arrangement of
said pixels or vice versa.

60. The display device according to one of
claims 52 to 54, wherein the grating has a gentle slope
and a steep slope in a cross section and the gentle
slope is directed to above a display screen of said
display device.